



## SMW-303 multiband, 3-cable WiFi MIMO/Diversity & GPS

- 3 antennas in 1 antenna housing
- Covers GPS, WiFi, Public Safety 4.9 & Military 4.4 GHz
- Saves time and money by reducing the number of installations
- Available in either Surface-mount (SMW Series or Mag-mount (MGW Series)

The SMW-303 Series Antenna provides multiband coverage on WiFi at 2.4 & 5 GHz, Public Safety at 4.9 GHz, Military at 4.4 GHz and GPS. It can also cover the UMTS band at 2.1 GHz or WiMAX at 2.3 GHz. The antenna is configured with 3 cables: one for GPS and the other two for the modems.

This surface mount multiband antenna mounts easily to a roof, trunk or bulkhead. The stud mount design uses a 3/4" feed thru (19mm) for securing to the vehicle.

The WiFi cables are 15 feet of low-loss RF-195 (4.5 meters). GPS cable is 15 feet of RF-174. All connectors are male unless otherwise requested.

For best performance, the antenna should be mounted on a metal surface or ground plane. A Mag-mount version is available with the same performance specs.

The antennas are enclosed in a 4.2"D x 3.2"H weatherproof ASA radome (107 mm x 81 mm) and supplied with all mounting hardware and a sealing gasket. The SMW Series is extremely weather resistant and rated IP67 for Dust and Water Ingress. The antennas have also passed industrial and military shock and vibration testing.

**Model Configurator**

SMW-303-----

Cable/Connector 1  
Cable/Connector 2  
Cable/Connector 3  
Color  
Cable Length in Inches (eg. 12 or 180)

Example: SMW-303-3C3C2C-WHT-180  
MGW-303-3C3C2C-BLK-180

Specify "SMWG" or "MGWG" instead of "SMW" or "MGW" for GPS/Glonass combination antenna.

Cable Options:		Connector Options:		Color Options:	
Code	Cable	Code	Connector	Code	Color
1	RG-58	A	TNC	WHT	White
2	RG-174	B	Mini UHF	BLK	Black
3	RF-195	C	SMA		

(Other Configurations available.)

### Specifications

Frequency & Gain (peak):		Cable:	
Cable 1	2.4-2.5 & 4.9-6.0 GHz, 5 dBi	Cable 1 & 2	Separate RF-195,15 ft (4.5 meters)
Cable 2	2.1-2.5 & 4.4-6.0 GHz, 5 dBi	Cable 3 (GPS)	RG-174, 15 ft (4.5 meters)
Cable 3 (GPS)	1575.42 +/- 2 MHz, LNA 26dB 5 dBi nominal RHCP, Antenna	Connectors:	SMA Plug (Male)
Data Modem:		Mounting:	Threaded metal stud 3/4" dia. x 1/2" long (19 mm x 13 mm) for 1/4" (6 mm) thick metal; supplied with gasket and nut
VSWR	2:1 max over range	Operating Temp:	-40° to +80° C
Nominal Impedance	50 ohms	Shock & Vibration:	IEEE1478, EN 61373, MIL-810G, TIA 329.2-C
Power	10 Watts	Dust/Water Ingress:	IP67
GPS:			
Noise Figure	2.0 dB max, 1.7 dB typica		
Amplifier Bias	2.7 to 5 VDC		
Amplifier Current	20 mA, 10 mA typical		
GPS & Glonass Option:	1575 MHz & 1612 MHz		
Case:	4.2"D x 3.2"H (107 mm x 81 mm) add 1/2" (13 mm) for mag base		
Case Material:	White or Black UV resistant ASA		