



MIMO CMD Series
mounted on ceiling panel



CM2 Series mounted on
ceiling panel

Ceiling Mount Antennas, Omni-directional, 2.4 & 5 GHz

- Antennas provide uniform omni coverage for indoor use
- Models available for WiFi, Bluetooth and 802.11a/b/g/n applications
- MIMO Ceiling Mount versions, 2 or 3 cables
- Models available with Fire Retardant cable (RF-195FR)

Mobile Mark's line of Ceiling Mount omni-directional antennas are designed for efficient distribution of inbuilding wireless coverage for WiFi, Telemetry and Hotspots.

The antennas mount to any ceiling that allows the cable to be routed above; dropped ceilings are perfect for this type of installation.

These antennas use a design that incorporates a quarterwave on a ground plane which enhances the peak lobes of these antennas. This unique design provides significant improvements in efficiency while being very economical.

The antennas maintain an omni pattern in the horizontal plane while VSWR performance is maintained across the operating bandwidth.

Several models are available including both single band and dual-band coverage at 2.4 & 5 GHz. A dual band model provides operation on the two popular bands simultaneously (one coax feed for both bands).

Two MIMO (Multiple-Input-Multiple-Output) models are available:

one is configured with two elements and the other with three elements. All of the elements are identical and all cover both 2.4 & 5 GHz bands. Each element is fed by a separate cable.

The MIMO radio style will determine if a 2-element or 3-element antenna should be used.

Model #	Frequency	Application
Single Cable		
CM2-2400-9C-WHT-12	2.4-2.5 GHz	802.11b/g
CM2-5500-9C-WHT-12	5-6 GHz	802.11a/ac
CM2-2400/5500-9C-WHT-12	2.4-2.5 GHz & 5-6 GHz	802.11a/b/g/n
MIMO 2 Cable		
CMD-W-9C9C-WHT-12	2.4-2.5 & 4.9-6.0 GHz	802.11a/b/g/n
MIMO 3 Cable		
CMD-W-9C9C9C-WHT-12	2.4-2.5 & 4.9-6.0 GHz	802.11a/b/g/n

Specifications			
Frequency:		Radome Material:	White ASA
CM2-2400	2.4-2.5 GHz	Weight:	1.0 lbs (0.5 kg)
CM2-5500	5-6 GHz	Dimensions:	3.5"D x 1.5"H (89 mm x 38 mm)
CM2-2400/5500	2.4-2.5 & 5-6 GHz	Mounting:	
CMD-W	2.4-2.5 & 4.9-6 GHz	CM2	(3) #8-32 machine screws
Gain:		CMD-W	2" L x 5/8" D threaded stud in flange, thru-hole feed for cable
CM2	2.5 dBi	Cables:	
CMD-W	4 dBi	CM2	1 ft. RF-195FR (30.5 cm)
VSWR:	2:1 over band	CMD-W	(2 or 3) 1 ft. (30.5 cm) RF-195FR
Nominal Impedance:	50 ohms	Termination:	SMA Plug (Male)
Max. Power:			
CM2	5 Watts		
CMD-W	20 Watts		
Beamwidth (-3 dB point):	70 degrees		
Operating Temp:	-40° to +85° C		