

LTMG308



PRODUCT OVERVIEW

The 3-cable LTMG308 antenna includes two Global 5G LTE elements and one GNSS element. This provides MIMO (multiple-input-multiple-output) coverage for the 5G ready Cellular band. In addition, GNSS operates on GPS, Galileo, Glonass, QZSS or Beidou.

The Global LTE 5G-ready antenna element covers: 617-960 & 1710-6000 MHz. Cellular coverage includes these bands: CBRS (Citizen Band Radio Service) at 3.55-3.7 GHz and Band 71 at 617-698 MHz.

This 3 element antenna is part of our 626 line with a wider frequency covering sub-6 & 5G Ready.

Specify LTM308 for a model configured with GPS only.

Visit our eStore to customize an Antenna Online.

| Electrical Specifications | | | |
|---------------------------|---------------------------|--|--|
| Frequency & Gain | | 617 - 960 MHz, 3 dBi 1710 - 6000 MHz, 4 dBi | |
| | | 1561, 1575, & 1602 MHz, LNA 26 dB, 5 dBi | |
| VSWR | 617 - 960 | < 2.2 MAX, < 2:1 TYP. | |
| | 1710 - 6000 | < 2:1 | |
| Impedance | 50 Ohm Nominal | | |
| Power Rating | 10 Watts | | |
| GNSS | Amplifier Gain | 16 dB | |
| | Amplifier Bias Voltage | 3 to 5 VDC | |
| | Noise Figure | 2.0 dB max, 1.5 dB typical | |
| | Current | 20 mA max, 10 mA typical | |

Mechanical Specifications

| | • | |
|-------------------------|--|--|
| Radome Material & Color | ASA UV-Inhibitive Plastic, Available in Black or White | |
| Radome Dimension | 5.5" (13.9 cm) in Diameter 2.38" (6.0 cm) in Height | |
| Standard Connectors | SMA Plugs (Male) | |
| Cables 1 & 2 | Separate LL-195, 15 ft (4.5m) | |
| GNSS Cable 3 | RG-174, 15 ft (4.5 m) | |
| Operating Temperature | -40° to +80° C | |
| Mounting | 7/8" (22.2 mm) Dia. Feed Through 3/4" (19 mm) Long Thread for Up to 1/2" (12.7 mm) Thick Surface | |
| Shock & Vibration | IEEE1478, EN61373, MIL-810G, TIA 329.2-C | |
| Water Ingress | IPX7 When Properly Mounted | |



MULTI-BAND ANTENNA

| L T M G 3 0 8 - <mark>3 C 3 C</mark> 2 C - W H | T - 1 2 0 | | |
|--|-----------|--|--|
| LTE Cables | | | |
| | | | |
| GNSS | | | |
| Color | | | |
| Cable Length (in inches) ——— | | | |

HIGHLIGHTS:

- Multiband:
- 2x LTE & 1x GNSS
- Covers Sub-6 5G Ready 617 - 6000 MHz Including CBRS & Band 71
- High Performance; High Gain
- Made-in-the-USA & UK

RELATED MODELS:

- LLPG308
- (Same Freq, Lower Profile) MXFG308
- (Same Freq, MaxFin Style) LTM308
- (GPS Model)

COMMON APPLICATIONS:

- Vehicle Fleet Management
- Multiband Modems
- Public Transportation



US Headquarters +1.847.671.6690 US/CA Toll Free +1.800.648.2800 European Facility +44.1543.459555