



DM Series in White



DM Series in Black



MGD Dual Band Mag

## Surface Mount & Mag-Mount 2.4 & 4.9-6.0 GHz

- Available in Single band 2.4 GHz and Dualband 2.4/4.9-6.0 GHz
- Ground plane independent omni configuration
- Rugged and attractive low profile ASA radome

The DM antennas provide a low profile style antenna that can be mounted to any vehicle, container or bulkhead. The rugged style is excellent for industrial applications, yet attractive for consumer use.

The unit has an elevated grip-lip for properly removing the antenna. The base is covered with protective vinyl sheet to prevent scratches.

Models are available in a stud mount (DM) or Mag Mount (MGD, dual band only).

The MGD Mag Antennas are outfitted with 10 feet (3 m) of low loss-195 cable and connector, typically SMA Plug (Male).

The DM stud mount Single band operates on the 2.4 GHz WiFi band, and the dual band Series on 2.4/4.9-6 GHz. These use a 5/8" (16mm) feed thru for securing to the vehicle. The antennas are outfitted standard with 1 foot (305 mm) of cable & connector, typically SMA Plug (Male).

Antenna performance is 2.0 dBi with no ground plane required. The antennas can even be mounted on fiberglass or plastic housing.

The antenna radome is available in white or black ASA. The bottom mounting plate is outfitted with a sealing gasket for a watertight seal.

The MGD Mag Mount is a dual band antenna (both 2.4 GHz & 4.9-6.0 GHz). It provides 2.5 dBi peak gain on either band. It has a powerful magnet for securing to an appropriate metal surface. The antenna has a 3.75" (95 mm) base.

Model #	Frequency
DM2-2400-3C-WHT-12	2.4-2.5 GHz
DM2-2400/5500-3C-WHT-12	2.4-2.5 & 4.9-6.0 GHz
MGD-2400/5500-3C-BLK-120	4.9-6.0 GHz
NT-MK	Heavy Duty Pole/Wall Mount
<u>Color options available:</u> Black - BLK and WHT-White	

Specifications	
Frequency:	See above
Gain:	2.5 dBi peak
VSWR:	2:1 max over range
Operating Temp:	-40° to +85° C
Nominal Impedance:	50 ohms
Maximum Power:	10 watts
Case Material:	White or black UV Resistant ASA plastic
<b>MGD Mag Unique Specs</b>	
MGD Mag Radome:	3 3/4" D x 1 7/8" H (95 mm x 48 mm)
MGD Cable:	RF-195, 10 ft (3m) & SMA Plug (Male)
<b>DM Stud Mount Unique Specs</b>	
DM Radome:	3" diameter x 1 1/2" high (76 mm x 38 mm)
Hardware Supplied:	Nut, lockwasher, gasket
DM Pigtail Cable :	RF-195, 1 ft (305 mm), SMA Plug
DM Mounting:	3/4" L stud (19 mm) 5/8" diameter (16 mm) feed thru for 1/2" thick surface (12.7mm)
Mounting Option:	Pole/Wall Mount adapter NT-MK
Jumper/Cable Option:	Use jumpers for longer length install or order with custom EN 61373, IEEE 1478, MIL -810G, TIA-329.2-C
Shock & Vibration:	
IP Rating	DM: IPx7